

# SW-1070/SW-20140



## Hybrid Control Panels

Two-way wireless control panels with additional wired zones giving you total flexibility without compromise. The panels can talk to a whole suite of devices including wireless PIR's, Sensors, Magnetic Contacts, Panic Buttons, Key-fobs, Smoke Detectors, Internal & External Sirens and more besides.

With both horizontal and vertical antennas you will be pleasantly surprised by its excellent RF range.

- 70 two-way wireless detectors\*
- 2 two-way wireless Internal Sirens\*
- 2 two-way wireless External Sirens\*
- 2 Repeater/Interfaces\*
- 64 two-way wireless Key-fobs\*
- SW-1070: comes with 10 on-board zones
- SW-20140: comes with 10 on-board zones plus a 10-zone expander
- SW-1070: 70 wired zones, fully expanded
- SW-20140: 140 wired zones, fully expanded
- 8-way block system with 1 common area
- SW-1070: 8 keypads & 6 expanders
- SW-20140: 8 keypads & 13 expanders
- All expander zones fully analysed

- SW-1070: 106 wired zones (with ID sensors/modules)
- SW-20140: 176 wired zones (with ID sensors/modules)
- 64 Users (7 SmartLink 7 remote users)
- SW-1070: Up to 217 programmable outputs
- SW-20140: Up to 231 programmable outputs
- Output Mapping
- 999 event engineer log
- Plug-on digi supporting SMS & Voice Messaging
- BS8243 and PD6662: 2010 Compliant
- Mains: 230Vac +/- 10%, 50Hz
- Output: 13.7Vdc +/- 0.2V
- Current Consumption: 75mA
- Current: 1.5A
- Temperature: -10 to +40°C
- Weight: 1,430g
- Size: 360mm x 236mm x 87mm
- EN 50131-1
- EN Grade 2
- Environmental Class II
- \* Up to 80 wireless devices in total

**SecureWave**  
868MHz Radio



Safe & Secure

www.hkc.ie

# Security

# RKP



## SW-RKP Slimline

Its slim profile is aesthetically designed to compliment modern interiors. It also features an easy to read graphical display.

The new generation RKP has a vastly bigger audio message library to choose from.

- Easy to install
- Up to 8 keypads per system
- High speed keypad bus
- Graphics LCD with blue back-lighting
- Audible word library
- Built-in panic feature; press \* and # together
- No DIP switch settings required
- Keyprox version available for BS8243
- Supply: 13.7Vdc
- Quiescent Current: 30mA
- Max. Current: 120mA
- Temperature: -10 to +40°C
- Weight: 245g
- Size: 167mm x 125mm x 26mm
- EN 50131-1
- EN Grade 2
- Environmental Class II

**Installer:**  
**Crosby Intruder Alarms**  
20 Endbutt Lane,  
Crosby,  
Liverpool,  
L23 0TR

**Tel:** 0844 588 6912  
**Fax:** 0844 589 6912

**Web:** [www.crosbyintruder.co.uk](http://www.crosbyintruder.co.uk)  
**Email:** [sales@crosbyintruder.co.uk](mailto:sales@crosbyintruder.co.uk)



**SecureWave**  
868MHz Radio

Safe & Secure

Thank you for considering HKC products for your security system.

For further information in relation to any of our products, please contact us at:

**HKC Ltd.**  
Parkway Business Centre, Ballymount,  
Dublin 24, Ireland.  
T: 353 1 456 7007  
F: 353 1 456 8332  
E: [sales@hkc.ie](mailto:sales@hkc.ie)  
UK Technical Support: 0800 111 4599

or visit us at [www.hkc.ie](http://www.hkc.ie)

[www.hkc.ie](http://www.hkc.ie)